







SPECIFICATIONS

Engine Type 4-Stroke, 4-Valve, DOHC Liquid-Cooled 149cc Displacement Bore X Stroke 57.3 x 57.8 (mm) Maximum Power 12.0 KW @ 8,000 rpm

Maximum Torque 13.7 Nm @ 7.000 rpm

Transmission Type Manual 6-Speed Constand Mesh

Fuel System PGM-Fi

Fuel Tank Capacity 12.0 L

Lighting System All LED Lighting

Starting System Electric

Inverted Telescopic Suspension Type (Front)

Suspension Type (Rear) Swing Arm with Monoshock (Pro-Link)

130/70 - 17 M/C 62P

Wheel Type Cast Wheel

Tire Size (Front) 100/80 - 17 M/C 52P

Brake System (Front) Hydraulic Disc

Brake System (Rear) Hydraulic Disc

Overall Dimensions: LxWxH 1,983 x 700 x 1,090 (mm)

Wheelbase 1,310 mm

151 mm **Ground Clearance**

Curb Weight 137 kg

Seat Height 788 mm

FEATURES



ASSIST/SLIPPER CLUTCH

Enables a lighter clutch lever pull for a smooth and accurate ride



INVERTED FRONT SUSPENSION

Stability and handling with a new superior look



LED HEADLIGHT AND FRONT WINKER

Illuminate your way with a sporty headlight design



TAIL LIGHT AND REAR WINKER

Bright dashing tail lights for maximum safety and style



POWERFUL 149CC.6-SPEED, DOHC LIQUID-COOLED ENGINE Fireblade inspired power for a world

class racing engine experience



FULL DIGITAL METER PANEL

Enhanced digital panel for a more precise information



BANK ANGLE SENSOR

Automatically turns off the engine when bank angle exceeds 60° for your daily safety

COLOR VARIANT



Winning Red (Honda Tri-Color)

Actual Unit May Vary



Tire Size (Rear)

Customer Care Hotline:

: 1-800-10HONDAPH-4663274 : customerservice@hondaph.com









www.hondaph.com



